(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 29 March 2001 (29.03.2001)

PCT

(10) International Publication Number WO 01/21690 A1

- (51) International Patent Classification7: 3/24, B32B 27/26, 25/12 // C08L 21:00
- C08J 5/12,
- (21) International Application Number: PCT/US99/21694
- (22) International Filing Date: 20 September 1999 (20.09.1999)
- -----

English

(25) Filing Language:
(26) Publication Language:

- English
- (71) Applicant (for all designated States except US): THE GOODYEAR TIRE & RUBBER COMPANY [US/US]; D/823, 1144 East Market Street, Akron, OH 44316-0001 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): PULFORD, Carl, Trevor, Ross [US/US]: 2504 8th Street, Cyuhaga Falls, OH 44221 (US). DING, Ran [CN/US]; 680 Norbury Drive, Hudson, OH 44226 (US). D'SIDOCKY, Kichard, Michael [US/US]: 3005 Clearview Road, Ravenna, OH 44266 (US). REILLY, Patrick, John [US/US]; 275 Afton Avenue, Akron, OH 44313 (US).

- (74) Agent: KRAWCZYK, Nancy, T.; D/823, The Goodyear Tire & Rubber Company, 1144 East Market Street, Akron, OH 44316-0001 (US).
- (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, CD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KF, KR, KZ, LC, LK, LR, LS, LT, LU, LY, MD, MG, MK, MM, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, Fl, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GR, GW, ML, MR, NE, SN, TD, TG).

Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BONDING ELASTOMERIC ARTICLES

O 01/21690 A

(57) Abstract: An improved method of bonding at least two cured or uncured elastomeric layers is disclosed. The method comprising placing an uncured elastomeric component (22) between the two elastomeric layers, and curing the elastomeric component to be printing the new productive component (22) by the printing the uncured elastomeric component (22) by the printing two non-productive compounds (10, 12), wherein each non-productive compound (10 or 12) is prepared with a co-teacting agent of a co-teacting cure package nor added to the other non-productive compound (12 or 10), and layering the non-productive elastomer compounds (10, 12) in alternating layers with a thickness relative to the diffusion rate of the co-reacting agents in each non-productive elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through the elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through the elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through the elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through the elastomeric layer (10, 12) to effect diffusion of the co-reacting user agents through the elastomeric layer (10, 12) to effect the elastomeric layer (10, 12) to e